K-LiTE Focus - Half Frame

The Bulk head are the perfect combination of aesthetic fixture design and optimum illumination performance. Surface mounting wall light for illumination of interior and exterior locations where guidance and security lighting is required.

Product Description

- · Luminaire made of die cast aluminium with non corrosive SS fasteners.
- Non yellowing UV stabilized translucent polycarbonate diffuser for glare free, uniform light distribution.
- · Silicone gasket.
- · Luminaire integrated with 12W LED.
- · Cable entries for through-wiring of mains supply cable.
- · Integral constant current power supply.
- CRI (Ra): >80.
- Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply.
- Ordering guide: KL-24046-CCT (Colour Temperature).
- Available CCT: 2700K, 3000K, 4000K, 5700K



Product Benefits

- · High luminous efficiency at reduced wattage.
- · Versatile use, Simple installation.
- Sustainable LED technology offers durability and optimal light output with low power consumption.

Area of Application

Suitable for Private & Public areas, Commercial centres, Walkways, Residential, Passages.

Available Finish

Pure polyester powder coated black



K-LiTE Focus - Half Frame





HOTEL DOLPHIN, VISAKHAPATNAM

Technical Specifications General

ID : 24046 System Wattage : 12W LED Driver Integral : Constant Current Operating Voltage : 100-277Vac

Opaerating Temperature :-15°C~+50°C

Physical

Body : Die Cast Aluminium Diffuser : Translucent Polycarbonate : Wall - Surface Mounting : Powder Coated Black Finish

Light Source

Light Source : NICHIA CRI (Ra) : >80

LED Colour Temperature : 2700K / 3000K / 4000K

5700K

Driver

Power Supply : Integral Input Voltage : 230-240Vac Frequency : 50-60Hz Power Factor :>0.95 THD :<10% Surge Protection :3KV Efficiency :>80%

Optical Performance

Beam Angle :120°



