



Technical Specifications

Light Source

Light Source	: LED
CRI (Ra)	: >90
LED Colour Temperature	: 2700K / 4000K (Special colours on request)

Physical

Body	: Extruded Aluminium
Mounting	: Surface
Finish	: RAL9016 Traffic White / RAL9004 Black / Anodized Aluminium

General

Driver	: Constant Voltage
Operating Temperature	: -15°C~+50°C
Operating Voltage	: 24Vdc
Power Supply	: Non Integral 24V PSU (IP67)

Specification

Power (W/m)	10W/m
Max.length (m)	2 mts
Max.serial run length (m)	5 mts
Max.ambient temp.(Ta _{max})	50°C

Optical

Tilt	: Fixed
Beam Angle	: 120° (Diffused)
Diffuser Material	: Translucent Polyurethane Encapsulation

- The given data are standard values. Due to tolerances of the manufacturing process and the electrical components, photometric values and electrical power can vary up to 10 - 12%.
- Luminous flux upto -40% with opal transmission.
- In IP67 encapsulated products, tolerance in colour temperature can occur.
- Light distribution refer online



Ordering Guide

Surface - Direct

ID	Wattage	Dimension (mm)
23247	5W	500 x 16 x 34
23247	10W	1000 x 16 x 34
23247	15W	1500 x 16 x 34
23247	20W	2000 x 16 x 34

Note : Luminaire operating voltage is 24Vdc, to be ordered with suitable power supply and accessories.